



# Standard Practice for Soil Sample Preparation for the Determination of Radionuclides<sup>1</sup>

This standard is issued under the fixed designation C 999; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

## 1. Scope

1.1 This practice covers the preparation of surface soil samples collected for chemical analysis of radionuclides, particularly uranium and plutonium. This practice describes one acceptable approach to the preparation of soil samples for radiochemical analysis.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.* A specific hazard statement is given in **Note 1**.

## 2. Referenced Documents

2.1 *ASTM Standards:*<sup>2</sup>

- C 998 Practice for Sampling Surface Soil for Radionuclides
- E 11 Specification for Wire Cloth and Sieve for Testing Purposes

## 3. Summary of Practice

3.1 Guidance is provided for the preparation of a homogeneous soil sample from ten composited core samples (aggregate weight of 4 to 5 kg) collected as to be representative of the area.

## 4. Significance and Use

4.1 Soil samples prepared for radionuclide analyses by this practice can be used to monitor fallout distribution from nuclear facilities. This practice is intended to produce a homogeneous sample from which a relatively small aliquot (10 g) may be drawn for radiochemical analyses.

4.2 Most nuclear facilities fulfill major requirements of their monitoring programs by gamma-ray spectrometry measurements of soil. A widely used practice for these measurements is to fill a calibrated sample container, such as a Marinelli beaker (~600-mL volume), with a homogenized soil sample. By preparing the entire soil core collection, sufficient homogeneous sample is available for radiochemical and gamma-ray spectrometry measurements.

## 5. Apparatus

- 5.1 *Scale*, capacity of 10 kg.
- 5.2 *Drying Oven*, able to maintain  $\pm 2^\circ\text{C}$ .
- 5.3 *Pans*, disposable aluminum.
- 5.4 *Jar Mill*, capacity for 7.57-L (2-gal) cans.
- 5.5 *Steel Cans and Lids*, 7.57-L (2-gal).
- 5.6 *Ceramic Rods*, 21 by 21-mm ( $1\frac{3}{16}$  by  $1\frac{3}{16}$ -in.) or steel grinding balls, 25.4-mm (1-in.) diameter.
- 5.7 *Sieve*, U.S. Series No. 35 (500- $\mu\text{m}$  or 32 mesh).
- 5.8 *Plastic Bottles*, 7.57-L (2-gal).

## 6. Procedure

- 6.1 Label a cleaned 7.57-L (2-gal) steel can and lid with a unique laboratory code number.
- 6.2 Weigh the labeled steel can and lid. Record the weight.
- 6.3 Transfer the ten soil cores (including vegetation) from the field collection containers into the labeled, preweighed steel can. Do not pack the can full. Place the steel lid loosely on the can.

**NOTE 1—Warning:** Wear gloves throughout the preparation procedure to minimize the possibility of fungus infection.

- 6.4 Weigh the sample cores, steel can, and lid to  $\pm 50$  g. Record the weight.
- 6.5 Remove the lid and place the sample in a  $110^\circ\text{C}$  drying oven for 24 h or longer, depending on the depth of soil in the can, until the sample has reached constant weight.
- 6.6 Remove the sample from the oven, cap the can with its lid, and cool to room temperature.
- 6.7 Weigh the dried sample cores, steel can, and lid to  $\pm 50$  g. Record the weight.

<sup>1</sup> This practice is under the jurisdiction of ASTM Committee C26 on Nuclear Fuel Cycle and is the direct responsibility of Subcommittee C26.05 on Test Methods.

Current edition approved June 1, 2005. Published June 2005. Originally approved in 1983. Last previous edition approved in 2000 as C 999 – 90 (2000).

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

6.8 Remove the can lid and add 10 to 12 ceramic rods (21 by 21-mm) or steel balls (25.4-mm diameter) to the can.

6.9 Replace the lid and tightly seal the sample can.

6.10 Place the sample can on a jar mill for at least 4 h, or overnight if possible, at 30 r/min.

6.11 Remove the sample can from the mill and place in a hood.

6.12 Allow the sample to settle for a few minutes.

6.13 Label a 7.57-L (2-gal) plastic jar and cap with the laboratory code number of the sample.

6.14 Remove the lid from the sample can and transfer a portion of the sample to a U.S. Series No. 35 (500- $\mu$ m or 32 mesh) sieve.

6.15 Sieve the sample and transfer the sieved fraction to the prelabeled plastic jar.

6.16 Repeat the sieving and transfer steps until the entire sample has been processed.

6.17 Remove the ceramic rods or steel balls from the unsieved material.

6.18 Place the unsieved material in the can and replace the lid.

6.19 Weigh, record the weight, and discard the unsieved material and can.

**NOTE 2—Caution:** The unsieved material should consist of rocks, stones, and sandy matter. If soil clumps remain, additional milling is required.

**NOTE 3—Caution:** The ceramic or steel grinding media and the sieve must be cleaned thoroughly prior to reuse to eliminate the possibility of cross-contamination of samples.

6.20 Remove a suitable aliquot of the sample from the jar for radiochemical analysis.

6.21 Cap the sample jar tightly. Wash and dry the outside of the container prior to storage.

## 7. Calculation

7.1 *Wet Weight of the Composited Soil Cores*—The wet weight ( $W$ ) of the composited soil cores is the weight measured prior to oven-drying the cores as follows:

$$W = T - C \quad (1)$$

where:

$W$  = wet weight of the composited soil cores, g,

$T$  = weight of the soil cores, steel can, and lid, g (from 6.4), and

$C$  = weight of the empty steel can and lid, g (from 6.2).

7.2 *Dry Weight of the Composited Soil Cores*—The dry-weight ( $D$ ) of the composited soil cores is the weight measured after drying the cores at 110°C as follows:

$$D = N - C \quad (2)$$

where:

$D$  = dry (110°C) weight of the soil cores, g,

$N$  = weight of the dried (110°C) soil cores, steel can, and lid, g (from 6.7), and

$C$  = weight of the empty steel can and lid, g (from 6.2).

7.3 *Bulk Density of the Soil Cores*—The bulk density ( $B$ ) of the soil cores may be estimated from the wet weight of the cores ( $W$ ) and the number of cores collected for compositing, times the volume of the sampling corer used in the field collection.

$$B = (W)/(F \times V) \quad (3)$$

where:

$B$  = bulk density of the composited soil cores, g/cm<sup>3</sup>,

$W$  = weight of the composited soil cores, g, (from 7.1),

$F$  = number of soil cores collected and composited (10 cores in accordance with Practice C 998), and

$V$  = volume of sampling corer used for the field collection, cm<sup>3</sup>.

7.4 *Weight of Unsieved Material*—The weight of the unsieved material, consisting primarily of rocks and stones, is obtained for documentation purposes.

## 8. Keywords

8.1 environmental; preparation; radionuclides; soil

## APPENDIX

### (Nonmandatory Information)

#### X1. RATIONALE

X1.1 A soil sampling and analysis program provides a direct means of determining the concentration and distribution pattern of radionuclides in the environs of nuclear facilities.<sup>3</sup>

X1.2 This practice was developed to minimize sample handling and economic costs while providing a final sample homogeneity adequate for the intended radiochemical analyses. For these reasons, the soil cores collected in the field are treated as a single sample without preliminary subdivision into arbitrary fractions, such as +2-mm or –2-mm sizes. Vegetation is not separated from the cores because it contributes little to the volume or bulk density of the sample. Rocks and stones allowed to remain in the sample during the milling operation act as additional grinding media. After the milling operation, the rocks and stones may be discarded because these materials would not contain radionuclides originating from a nuclear facility release.

X1.3 The milling of the soil to No. 35 (500- $\mu$ m or 32 mesh, see [Table X1.1](#)) sieve size is based on consideration of the particle size of plutonium present in soil at three sites of releases. Tamura<sup>4</sup> developed empirical information which shows that essentially 100 % of the plutonium is present in the No. 35 sieve fraction. Also see Specification [E 11](#).

<sup>3</sup> “Measurements of Radionuclides in the Environment: Sampling and Analysis of Plutonium in Soil,” Atomic Energy Commission Regulatory Guide 4.5, May 1974.

<sup>4</sup> Tamura, T., “Physical and Chemical Characteristics of Plutonium in Existing Contaminated Soils and Sediments,” Proceedings of the Symposium on Transuranium Nuclides in the Environment, IAEA Pub ST1/PUB/410, Vienna, 1976.

**TABLE X1.1 Various Sieve Size Designations**

U.S. Series Designation		Tyler Screen Scale Equivalent	Sieve Opening, in. (approximate equivalent)
Alternative	Standard		
No. 4	4.75 mm	4 mesh	0.187
No. 6	3.35 mm	6 mesh	0.132
No. 8	2.36 mm	8 mesh	0.0937
No. 10	2.00 mm	9 mesh	0.0787
No. 12	1.70 mm	10 mesh	0.0661
No. 14	1.40 mm	12 mesh	0.0555
No. 16	1.18 mm	14 mesh	0.0469
No. 18	1.00 mm	16 mesh	0.0394
No. 20	850 $\mu$ m	20 mesh	0.0331
No. 30	600 $\mu$ m	28 mesh	0.0234
No. 35	500 $\mu$ m	32 mesh	0.0197
No. 40	425 $\mu$ m	35 mesh	0.0165
No. 45	355 $\mu$ m	42 mesh	0.0139
No. 50	300 $\mu$ m	48 mesh	0.0117
No. 60	250 $\mu$ m	60 mesh	0.0098
No. 70	212 $\mu$ m	65 mesh	0.0083
No. 80	180 $\mu$ m	80 mesh	0.0070
No. 100	150 $\mu$ m	100 mesh	0.0059
No. 120	125 $\mu$ m	115 mesh	0.0049
No. 140	106 $\mu$ m	150 mesh	0.0041
No. 170	90 $\mu$ m	170 mesh	0.0035
No. 200	75 $\mu$ m	200 mesh	0.0029
No. 230	63 $\mu$ m	250 mesh	0.0025
No. 270	53 $\mu$ m	270 mesh	0.0021
No. 325	45 $\mu$ m	325 mesh	0.0017

*ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.*

*This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.*

*This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).*