



Standard Practice for Least Cost (Life Cycle) Analysis of Concrete Culvert, Storm Sewer, and Sanitary Sewer Systems¹

This standard is issued under the fixed designation C 1131; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This practice covers procedures for least cost (life cycle) analysis (LCA) of materials, systems, or structures proposed for use in the construction of concrete culvert, storm sewer, and sanitary sewer systems.

NOTE 1—As intended in this practice, examples of analyses include, but are not limited to the following: (1) materials—pipe linings and coatings, concrete wall thicknesses, cements, additives, etc.; (2) systems—circular pipe, box sections, multiple lines, force mains, etc.; and (3) structures—wet and dry wells, pump and lift stations, etc.

1.2 The LCA method includes costs associated with planning, engineering, construction (bid price), maintenance, rehabilitation and replacement, and cost deductions for any residual value at the end of the proposed project design life.

1.3 For each material, system, or structure, the LCA method determines in present value constant dollars, the total of all initial and future costs over the project design life, and deducts any residual value.

1.4 Major factors in the LCA method include project design life, service life, and relevant interest and inflation rates.

2. Referenced Documents

2.1 ASTM Standards:

E 833 Terminology of Building Economics²

3. Terminology

3.1 Definitions:

3.1.1 *constant dollars*—dollars of uniform purchasing power exclusive of inflation or deflation.

3.1.1.1 *Discussion*—Constant dollars are costs stated at price levels for a specific reference year, usually the particular time that the LCA is being conducted.

3.1.2 *current dollars*—dollars of purchasing power in which actual prices are stated, including inflation or deflation.

3.1.2.1 *Discussion*—Current dollars are costs stated at price levels in effect whenever the costs are incurred. In the absence of inflation or deflation, current dollars are equal to constant dollars.

3.1.3 *direct costs*—the direct costs of excavation, removal, and disposal of existing materials, systems, or structures; installation and testing of replacements materials, systems or structures; backfill; and surface restoration.

3.1.4 *discount rate*—accounts for the time value of money and reflects the impartiality of paying or receiving a dollar now or at a future time.

3.1.4.1 *Discussion*—The discount rate is used to convert costs occurring at different times to equivalent costs at a common time. Discount rates may be expressed in nominal or real terms.

3.1.5 *future costs*—costs incurred after a project has been constructed and operating, such as maintenance, rehabilitation, and replacement costs.

3.1.6 *indirect costs*—the costs of traffic rerouting, safety, utility relocations, etc., and additional future costs required by new land uses, population growth, etc.

3.1.7 *inflation rate*—an increase in the volume of money and credit relative to available goods and services resulting in a continuing rise in the general price level.

3.1.7.1 *Discussion*—In this practice, inflation refers to yearly change in the Producer Price Index (1).³

3.1.8 *interest rate*—the cost of borrowed money.

3.1.9 *maintenance costs*—the annual or periodic direct and indirect costs of keeping a material, system, or structure functioning for the project design life; such maintenance does not extend the service life of the material, system, or structure.

3.1.10 *nominal discount rate*—a discount rate that takes into account both the effects of inflation and the real earning potential of money invested over time.

3.1.10.1 *Discussion*—When future costs and values are expressed in current dollars, after having been adjusted for inflation, a nominal discount rate is used to convert the future costs and values to present value constant dollars. Users of this practice should consult with their accountant or client to determine the appropriate discount rate for a given project.

3.1.11 *original costs*—costs incurred in planning, designing, and constructing a project.

3.1.12 *project design life*—the number of years of useful life the material, system, or structure must provide.

3.1.13 *real discount rate*—a discount rate that takes into account only the real earning potential of money over time and

¹ This practice is under the jurisdiction of ASTM Committee C13 on Concrete Pipe and is the direct responsibility of Subcommittee C13.05 on Least Cost Analysis.

Current edition approved April 15, 1995. Published June 1995.

² *Annual Book of ASTM Standards*, Vol 04.07.

³ The boldface numbers refer to the list of references at the end of the standard.

is the differential between the interest and inflation rates.

3.1.13.1 *Discussion*—When future costs and values are expressed in future constant dollars, a real discount rate is used to convert constant dollars to present value dollars. Life cycle economic analyses conducted in constant dollars and a real discount rate are often preferred to similar analyses conducted in current dollars using nominal discount rates because no forecast of the inflation rate is required.

3.1.14 *rehabilitation costs*—the direct and indirect costs of rehabilitating a material, system, or structure to extend the service life of the material, system, or structure.

3.1.15 *replacement costs*—the direct and indirect costs of replacing a material, system, or structure before the end of the project design life, so it will again function as originally intended.

3.1.16 *residual value*—the remaining value of the material, system, or structure at the end of the project design life.

3.1.17 *service life*—the number of years of service a material, system, or structure will provide before rehabilitation or replacement is required.

3.1.17.1 *Discussion*—Project design life and service life are usually established by the owner or controlling agency.

4. Significance and Use

4.1 The significance of the LCA method is that it is a comprehensive technique for taking into account all relevant monetary values over the project design life and provides a measure of the total cost of the material, system, or structure.

4.2 The LCA method can be effectively applied in both the preconstruction and bid stages of projects. After bids are taken, real costs can be used instead of estimates.

5. Procedures

5.1 The procedures for determining the LCA of a material, system, or structure can be summarized in five basic steps.

5.1.1 *Identify Objective, Alternatives, and Constraints.*

5.1.2 *Establish Basic Criteria.*

5.1.3 *Compile Data.*

5.1.4 *Compute LCA for Each Material, System, or Structure.*

5.1.5 *Evaluate Results.*

5.2 *Objectives, Alternatives, and Constraints*—Establish the specific objectives of the project and identify alternative ways of accomplishing the objectives. For example, alternatives for a sanitary sewer system may include a gravity flow system versus a gravity flow system with life stations versus a single force main. Identify constraints, such as maximum culvert head or tail water, maximum and minimum slopes and depths of burial, installation methods, etc.

5.3 *Criteria*—Establish basic criteria that should be followed in applying the LCA method, including project design life; the material, system, or structure service life; direct and indirect costs and timing of maintenance, rehabilitation and replacement; real or nominal discount rate; and the comprehensiveness of the LCA evaluation.

5.4 *Compile Data*—Compile basic data required to compute the LCA of potential alternatives, including costs of planning, design, engineering and construction; maintenance costs; rehabilitation costs; replacement costs; residual values; and the

time periods for all future costs.

5.5 *Compute LCA*—The LCA of a material, system, or structure can be formulated in simple terms with all costs and values in present value constant dollars:

$$LCA = C - S + \Sigma(M + N + R) \quad (1)$$

where:

C = original cost,

S = residual value,

M = maintenance cost,

N = rehabilitation cost, and

R = replacement cost.

5.5.1 *Original Cost*—Original cost is defined in Section 3 and is normally developed from the engineer's estimate or is the actual bid price. A material, system, or structure may have a service life longer than the project design life and, consequently, would have a residual future current dollar value, which must be discounted back to a present constant dollar value, and subtracted from the original cost. Since maintenance, rehabilitation, and replacement costs may be incurred several times during the life of the project, the future current dollar value of each occurrence must be discounted back to a present constant dollar value and the values summed.

5.5.2 *Future Costs*—Future costs are normally estimated in constant dollar values, which are then converted to future current dollar values by an inflation factor and then discounted back to present constant dollar values by an interest factor:

$$FV = A(1 + I)^n \quad (2)$$

where:

FV = future current dollar value,

A = constant dollar value,

I = inflation rate, and

n = number of years in the future at which costs are incurred.

$$PV = \frac{FV}{(1 + i)^n} \quad (3)$$

where:

PV = present constant dollar value, and

i = interest or nominal discount rate.

Combining Eq 2 and Eq 3:

$$PV = A \left(\frac{1 + I}{1 + i} \right)^n \quad (4)$$

Eq 4 is usable, but requires assumptions of both interest and inflation rates. Although interest and inflation rates can vary widely, historical records indicate that the differential between interest and inflation rates has been relatively stable over the long term. Therefore, by defining an inflation/interest factor, F , as:

$$F = \left(\frac{1 + I}{1 + i} \right) \quad (5)$$

where:

F = inflation/interest factor.

Restating Eq 4:

$$PV = A (F)^n \quad (6)$$

The inflation/interest factor is virtually constant for specific

differentials between interest and inflation rates. Therefore, utilizing the inflation/interest factor in present value calculations eliminates the uncertainties and distortions due to selection of possibly incompatible individual interest and inflation rates (2).

NOTE 2—Table X1.1 presents the inflation/interest factor for a range of inflation rates from 4 through 18 % and differentials between interest and inflation rates of 1 through 5 %. For different sources of financing, the differential between interest and inflation rates significant in construction over a 30-year period is presented in Table X1.2.

5.5.3 Residual Value—If a material, system, or structure has a service life greater than the project design life, it would have a residual future current dollar value, which should be discounted back to a present constant dollar value and subtracted from the original cost. Using a straight-line depreciation, the present value of the residual value is:

$$S = C(F)^{n_p} \left(\frac{n_s}{n} \right) \quad (7)$$

where:

- S = residual value,
- C = present constant dollar cost,
- n_s = number of years the material, system, or structure service life exceeds the project design life,
- n = service life, and
- n_p = project design life.

With a lack of data to determine the residual value, a salvage value or cash value may be substituted or the term neglected. If accounting practices dictate, another depreciation method, other than straight-line, may be used.

5.5.4 Maintenance Costs—The present value of maintenance costs is calculated by determining the future value of each cost occurrence, discounting each to a present value, and summing all the values. Maintenance costs may be on an annual basis or estimated as a total for a periodic cycle or covering a certain number of years, which reduces the number of computations. The total present value of all maintenance costs is:

$$M = C_M \Sigma (Fn + F^{2n} \dots + F^{mn}) \quad (8)$$

where:

- M = total present value of all maintenance costs,
- C_M = constant dollar cost of a maintenance cycle,
- n = number of years in maintenance cycle, and
- m = number of maintenance cycles in project design life.

If a maintenance cycle ends in a year in which rehabilitation or replacement work is scheduled, then the total present value of maintenance costs should be refined by omitting the costs of

that maintenance cycle. Where future maintenance costs are on an annual basis, the total present value of all maintenance costs can be determined by:

$$M = C_M \left[\frac{1 - (F)^{MN}}{1/F - 1} \right] \quad (9)$$

5.5.5 Rehabilitation Costs—If a material, system, or structure has durability or structural problems before the end of the project design life, it may be possible to extend its service life by rehabilitation repairs. If the extended service life does not equal or exceed the project design life, the material, system, or structure would probably require replacement at the end of the extended service life. A material, system, or structure may require rehabilitation or replacement several times during the project design life. The present value of rehabilitation costs is calculated by determining the future value of each cost occurrence, discounting each to a present value and summing all values:

$$N = \Sigma C_N F^n \quad (10)$$

where:

- N = present value of rehabilitation costs,
- C_N = constant dollar cost estimated for a rehabilitation project,
- n = number of years after the project is completed that rehabilitation costs will be incurred.

5.5.6 Replacement Costs:

5.5.6.1 The present value of replacement costs is zero for a material, system, or structure with a service life equal to or greater than the project design life.

5.5.6.2 The present value of replacement costs for a material, system, or structure with a service life less than the project design life is calculated by determining the future value of each replacement, discounting each to a present value, and summing all values:

$$R = \Sigma C_R F^n \quad (11)$$

where:

- R = present value of replacement costs,
- C_R = constant dollar cost of replacement, and
- n = number of years after the project is completed that replacement costs are estimated to occur.

6. Keywords

6.1 acceptance criteria; concrete; costs; culvert; inflation rate; interest rate; least cost analysis; life cycle analysis; pipe; procedures; project design life; sanitary sewer; service life; storm sewer

APPENDIX

(Nonmandatory Information)

X1. INFLATION/INTEREST FACTOR

X1.1 *History*—The use of the inflation/interest factor to simplify life-cycle cost estimation was first proposed by the Jet Propulsion Laboratory of California Institute of Technology under a contract with the National Aeronautics and Space Administration (2). Kerr/Ryan proposed the concept for pipeline installations (3, 4), and developed the concept that the differential between interest and inflation rates for projects involving state or local funding should be determined using the municipal bond rate average, projects involving federal funding should be determined by the treasury bill rate average, and projects involving private funding should be determined by the prime lending rate. Subsequently, the American Concrete Pipe Association sponsored development of a comprehensive LCA microcomputer program, which is available from McTrans (5). The rehabilitation and replacement sections of LCA were developed primarily from Federal Highway Administration information on risk analysis, accidents, injuries, and deaths related to such projects (6, 7).

X1.2 Inflation/Interest Factor Values:

X1.2.1 Table X1.1 presents the maximum, minimum, and average values for the inflation/interest factor, F , as defined by Eq 5, for inflation rates ranging from 4 through 18 % and differentials between interest and inflation rates ranging from 1 through 5 %. The calculations show that the inflation/interest factor is virtually constant for specific differentials between the

TABLE X1.1 Inflation/Interest Factor Values

$(i - l) \%$	$F = (1 + l)/(1 + i)$		
	Maximum	Minimum	Average
1	0.9916	0.9905	0.991
2	0.9833	0.9811	0.982
3	0.9752	0.9720	0.974
4	0.9672	0.9630	0.965
5	0.9593	0.9541	0.957

rates. Values for inflation rates or differentials not shown in the table can be easily calculated.

X1.2.2 Table X1.2 presents 30-year averages of the inflation/interest factor and corresponding interest/inflation rate differential for municipal bonds, treasury bills, and the prime rate (4). Users of this practice can prepare similar tables as desired to update the factors, extend the 30-year period, or use indicators rather than municipal bonds, treasury bills, or the prime rate.

TABLE X1.2 Inflation/Interest Factor 30-Year Averages

Funding Source (User)	$F = (1 + l)/(1 + i)$	Differential $(i - l) \%$
Municipal Bonds (State and Local)	0.9953	0.52
Treasury Bills (Federal Agency)	0.9853	1.66
Prime Rate (Private Investment)	0.9749	2.86

REFERENCES

- (1) *Producer Price Index, Annual Averages*, U.S. Department of Labor, Bureau of Labor Statistics.
- (2) "Simplified Life-Cycle Cost Estimation," National Aeronautics and Space Administration, NASA Tech Brief, Vol 7, No. 1, Item 88, January 1983.
- (3) Kerr, W. O., and Young, A., *Interest and Inflation Factors in Least Cost Analysis*, published by American Concrete Pipe Association, Vienna, VA, 1985.
- (4) Kerr, W., and Ryan, B. A., "Taking the Guesswork Out of Least Cost Analysis," *Consulting Engineer*, March 1986.
- (5) LCA diskette, User Manual and Supplemental Documentation, McTrans, University of Florida, Center for Microcomputers in Transportation, Gainesville, FL 36210.
- (6) "The Design of Encroachments on Flood Plains Using Risk Analysis," Federal Highway Administration, HEC No. 17, 1980.
- (7) "Sensitivity of Resource Allocation Models to Discount Rate and Unreported Accidents," Federal Highway Administration, FHWA/RD-85/092, July 1985.

The American Society for Testing and Materials takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).