



Standard Specification for Impervious Graphite Pipe and Threading¹

This standard is issued under the fixed designation C 662; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 The purpose of this specification is to standardize the pipe sizes and types of threads used to join impervious graphite pipe and fittings. The thread standards may also be applied to impervious carbon pipe and fittings. It is limited to physical dimensions.

2. Terminology

2.1 Definitions of Terms Specific to This Standard:

2.1.1 *impervious graphite*—manufactured graphite that has been impregnated with a resinous material to make the final article impervious to liquids in the recommended operating range.

2.1.2 *impervious carbon*—the same as impervious graphite with the exception that the base stock has not been graphitized.

3. Requirements for Impervious Graphite Pipe

3.1 The eight standard pipe sizes are shown in Table 1 with permissible variations in dimensions.

3.2 Fig. 1 gives the male thread dimensions for impervious graphite pipe.

3.3 Fig. 2 gives the female thread dimensions for impervious graphite fittings.

4. Keywords

4.1 impervious carbon pipe; impervious graphite pipe; threading specifications

¹ This specification is under the jurisdiction of ASTM Committee D02 on Petroleum Products and Lubricants and is the direct responsibility of Subcommittee D02.F on Manufactured Carbon and Graphite Products.


Current edition approved Oct. 2, 1970. Published December 1970. Originally published as C 662 – 70. Last previous edition C 662 – 70 (1980).

TABLE 1 Physical Dimensions of Impervious Graphite Pipe

Pipe Size (nominal Inside Diameter), in.	Typical Limits								Length ^A	
	Inside Diameter				Outside Diameter					
	min		max		min		max		in. +¼ -0	mm +60 -0
	in.	mm	in.	mm	in.	mm	in.	mm		
1	1 ⁵ / ₁₆	23.8	1 ⁷ / ₁₆	27.0	1 ³¹ / ₆₄	37.7	1 ⁹ / ₁₆	39.7	108	2740.
1½	1 ⁷ / ₁₆	36.5	1 ⁹ / ₁₆	39.7	1 ⁶¹ / ₆₄	49.6	2 ¹ / ₁₆	52.4	108	2740.
2	1 ¹⁵ / ₁₆	49.2	2 ¹ / ₁₆	52.4	2 ¹¹ / ₁₆	68.3	2 ¹³ / ₁₆	71.4	108	2740.
3	2 ¹⁵ / ₁₆	74.6	3 ³ / ₄	82.6	4	101.6	4 ³ / ₁₆	106.4	108	2740.
4	3 ¹⁵ / ₁₆	100.0	4 ³ / ₄	108.0	5 ¹ / ₄	133.4	5 ¹ / ₂	139.7	108	2740.
6	5 ¹⁵ / ₁₆	150.8	6 ³ / ₄	158.8	7 ⁷ / ₁₆	188.9	7 ¹³ / ₁₆	198.4	108	2740.
8 ^B	8 ⁷ / ₁₆	204.8	8 ⁹ / ₁₆	208.0	9 ¹ / ₂	241.3	9 ³ / ₄	247.7	72	1830.
10 ^B	10 ¹ / ₁₆	255.6	10 ³ / ₁₆	258.8	12 ¹ / ₂	317.5	12 ³ / ₄	323.9	72	1830.

^A Maximum curvature—½% of length measured chord to arc.


^B Machined limits for 8 and 10 in. size pipe. All others are extruded to size.



Pipe Size	1	1½	2	3	4	6	8	10
A	1	1½	2	3	4	6	8½	10½
B	1½	2	2¾	4	5¼	7½	9½	12¾
D	⅜	⅜	⅝	⅝	⅝	⅝	⅝	⅝
E	1 ⁹ / ₁₆	1 ⁹ / ₁₆	1 ¹ / ₁₆	1 ¹ / ₁₆	1 ¹ / ₁₆	1 ⁹ / ₁₆	1 ¹⁵ / ₁₆	2 ³ / ₁₆
J max	1.436	1.906	2.589	3.899	5.149	7.319	9.426	12.419
min	1.430	1.898	2.581	3.887	5.137	7.306	9.412	12.404
K max	1.490	1.960	2.670	3.980	5.230	7.400	9.507	12.500
min	1.478	1.948	2.654	3.964	5.214	7.384	9.491	12.484
Threads per inch	12	12	8	8	8	8	8	8
Thread depth	0.0541	0.0541	0.0812	0.0812	0.0812	0.0812	0.0812	0.0812 ^A

^A Standard metric threads have not been established for impervious graphite pipe.

FIG. 1 Standard Male Thread Dimensions, (in.)^A



Pipe Size	1	1½	2	3	4	6	8	10
A	1	1½	2	3	4	6	8½	10½
C	1	1	1¼	1½	1½	1¾	2½	2¾
F	1⅝	2⅝	2⅞	4¼	5⅞ ₁₆	7⅞ ₁₆	9⅞	12⅞
G max	1.429	1.899	2.588	3.898	5.148	7.318	9.425	12.418
min	1.420	1.890	2.575	3.885	5.135	7.305	9.412	12.406
H max	1.462	1.934	2.637	3.951	5.201	7.372	9.480	12.474
min	1.456	1.926	2.629	3.939	5.189	7.359	9.466	12.459
Threads per inch	12	12	8	8	8	8	8	8
Thread depth	0.0449	0.0449	0.0674	0.0674	0.0674	0.0674	0.0674	0.0674 ^A

^A Standard metric threads have not been established for impervious graphite pipe.

FIG. 2 Standard Female Thread Dimensions, (in.)^A

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).